



# TerraGrip

## Technical Data Sheet

### Product Description

**TerraGrip** is a slip resistant additive that can be added to most aiflooring coatings to provide a fine texture and slip-resistance.

### Features and Benefits

**Anti-slip:** Provides a textured surface to minimize slip while maintaining cleanability

**Low Density:** Maintains suspension when added directly into the coating.

### Applications

- Damp Areas
- Stairs
- Inclines
- Unloading Areas
- Walkways
- Garages

### Application Overview

#### TerraChip System

Add 16-32oz. per 3 gallons of A+B final clear coat before application. Squeegee at a rate of 125-250 sq. ft./gallon and back roll.

#### TerraSeal

Add 16-32oz. per 3 gallons of A+B before application. -- Squeegee to a coverage of 175-200 sq. ft./gallon and roll.

### Warranty

American Industrial warrants its products to be free of defects in material and workmanship. This warranty specifically excludes the following: problems due to irregularities in the substrate, failures caused by moisture migration through the substrate, changes in color and gloss. Claims must be made within 12 months of installation of material.

### Safety

This product is intended to be installed by experienced professionals. Read the MSDS and product label for complete safety information before using. Avoid contact with all materials to prevent irritation. Use only with adequate ventilation.

Safety glasses, gloves, and protective clothing should be worn at all times while handling this product. Avoid exposure to eyes and skin as epoxy resins and hardeners can cause mild to severe skin irritation.

### Physical Properties

<b>Material</b> (ASTM D-4541)	micronized polymer
<b>Melting Point</b> (ASTM D-2240)	330°F
<b>Density</b> (ASTM D-4060)	0.90 cs-17 wheels, etc
<b>Particle Size</b>	840 microns (max) 20 mesh

The technical data and suggestions presented here are believed to be reliable and accurate at the time of publication. American Industrial makes no warranty, expressed or implied, based on this literature. Published technical data and recommendations are subject to change without notice.